

Trade Name: Majumdar Yellow

1. Identification of substance / preparation and of the company / undertaking -

- Product details *Use : Colourant

Trade name : Majumdar Yellow

- Manufacturer / Supplier

Manufacturer : 3, Sarkar Bye Lane, P.O:Burrabazar,

P.S: Girish Park, Kolkata- 700007

Ph: +91 9831004020

- Informing Department : Pigment Technical Services (PTS)

- Emergency Information : Phone No. +91-20-26127334

2. Composition / Information on ingredients -

- Chemical characterization : Coprecipitate of Cadmium Sulphide and Zinc Sulphide

Cadmium (Total): 85-90%; Zinc: 2-5%

- Identification number(s) -

C. I. Name : Pigment Yellow 35

C. I. No.(Principal Pigment): 77205

CAS No. Designation : 8048-07-5 / 12442-27-2

EINECS Number : ____

TSCA Number : 8048-07-5 / 12442-27-2

- Dangerous components :

<u>CAS No.</u> <u>EC No.</u> <u>Designation</u> <u>Percentage</u> <u>Index</u> <u>R-phrases</u>

None

3. Hazards Identification -



Trade Name: Majumdar Yellow

No labeling with symbols T+, T, C, Xn or Xi as per EU Directive 67/548/EEC. The usual precautionary measures for dealing with chemicals should be observed. On contact with strong acids, hydrogen sulphide is produced.

4. First Aid Measures -

- General Information : No special measures required.

- On inhalation : If inhaled move to fresh air, aid in breathing. If necessary, get

medical attention.

- On skin contact : Wash affected skin with soap and water.

- On contact with eyes : Flush eyes with plenty of flowing water. If irritation develops

consult oculist.

- On ingestion : If swallowed, rinses mouth and then drink plenty of water. Dilute

with water and induce vomiting. Get immediate medical attention.

5. Fire Fighting Measures -

- Suitable extinguishing agent/s : Water mist, extinguishing powder and CO₂

- Special exposure hazards : After combustion likely chances of gases like oxides of Carbon,

Cadmium, Zinc, sulphur and Nitrogen.

- Special Protective equipment for

Wear self contained breathing apparatus and wear full protective

fire-fighters : suit.

6. Accidental Release Measures -

- Person related safety precautions : Do not ingest or breathe in. Avoid contact with eyes and skin.

- Measures for environmental Prevent contamination of drains, surface waters, and soil. Pigment

protection : is generally insoluble in water.

- Method for cleaning up / collecting: Collect mechanically. Dispose off contaminated material as waste



Trade Name: Majumdar Yellow		
		according to item 13. Clean accident area carefully. Use warm water and cleaning agent.
7.	Handling and Storage -	
-	Handling :	Prevent formation of dust. Take precautionary measure against electrostatic charges – Earthing is necessary during loading operation. Avoid exposure to open flame or spark.
-	Storage :	 A moderately dry, well-ventilated area is considered to be adequate for handling and storage. Use proper personal equipment during handling. Protect from extreme heat and cold. Keep away from sources of ignition. Avoid dust formation.
-	Specific Use :	Used as colouring matter in paints, printing inks and plastics.
8.	Exposure Controls and Personal	Protection -



Trade Name: Majumdar Yellow

Additional information about design No further data. (see Sr. No. 7)

of technical system

- Exposure limit values : 15 μg Cd/l urine

1.5 µg Cd/100ml blood

- Personal protective equipments : Use safety goggles, aprons and gloves.

- General protective and hygienic The usual precautionary measures should be adhered to in handling

measures : the chemicals.

- Breathing equipment : Use air purifying equipment

- Hand protection : Wear rubber gloves.

Eye protection : Wear safety goggles or safety glasses.

- Skin protection : Impervious clothing.

9. Physical and Chemical Properties -

- Form : Powder - Colour : Yellow

- Smell : Odorless

- pH : Neutral

- Boiling point / Boiling range : Not applicable

Melting point / Melting range : Not applicable

- Flash point : Not applicable

- Ignition temperature : Not known

- Flammability : Not applicable

- Organic Solvents : EU/VOC 20°C : 0%

- Danger of explosion : Product is not explosive. However, formation of air / dust mixture

is possible.

Oxidizing property : Not applicable



Trade Name: Majumdar Yellow

Vapour pressure : Not applicable

- Relative density : 4.4

Water solubility : InsolubleSolvent solubility : Insoluble

- Partition coefficient : Not applicable

(n-Octanol / Water)

Viscosity : Not applicable
 Vapour density : Not applicable
 Evaporation rate : Not applicable
 Auto ignition temperature : Not known

10. Stability and Reactivity -

- Stability of product : This product is stable under normal storage condition.

Dangerous reaction : Risk of dust explosion.

- Materials to avoid : Exposure to strong acids, bases and oxidizing agents should be

avoided, which otherwise will generate hydrogen sulphide.

- Dangerous product of decomposition Toxic gases like SO₂ / vapors may evolve.

11. Toxicological Information -

- Acute toxicity : LD50/oral/rat - \geq 5000 mg/kg

- Primary irritant effect -

on the skin : Mild irritation on the eyes : Mild irritation

- Sensitisation : No sensitization. May cause skin sensitization to specially sensitive

person.

- Mutagenicity : Not known

- Additional toxicology information : When used and handled according to specification, the product does



Trade Name: Majumdar Yellow

not have any harmful effects according to our experience and

available information.

12. Ecological Information -

- Other information : Due to insolubility of the product in water a biodegradation is not

likely.

- Behaviour in environmental system:

- Ecotoxical effects -

Toxicity to fish : Data not available

Toxicity to daphnids (acute): Data not available

- AOX indication :

(Remark – The product is anticipated to be substantially removed by mechanical treatment)

- Mobility - Surface tension : Not applicable

Absorption : Not applicable

Desorption : Not applicable

- Persistence & Degradability : This pigment is considered to be generally insoluble in water,

biodegradability is not likely.

- Bioaccumulative potential : Not known

13. Disposal Information -

- Consult local expert for advice on the disposal.

- Waste disposal should be carried according to local and state regulation.

14. Transport Information -



Trade Name: Majumdar Yellow

- UN No. : None

GGV IMDG Code : NoneRID / ADR : None

- ICAO / IATA-DGR : None

- Custom Tariff No. : 32063000

15. Regulatory Information -

- Designation according to EC

guidelines : Not classified as "dangerous".

- Code letter and hazard designation

of product : Not classified as "dangerous".

16. Other Information -

.



Trade Name: Majumdar Yellow

Environmental Concerns -

Cadmium pigments are insoluble, even in dilute acids. The insolubility is further enhanced when the pigments are incorporated into polymers, typically at a 1 % loading. Pigments and pigmented articles are considered to be safe for landfill disposal. In a study of municipal solid waste incinerators (10), the cadmium concentrations found in ash leachates were below the maximum specified for drinking water in the USA. Incineration of polymers pigmented with up to four times the usual concentration of cadmium showed that these products have no significant impact on incinerator emissions (11). Cadmium and its compounds have been classified as List 1 substances in EU-Directive 76/464/EEC relating to pollution of the aquatic environment, and E.U. member states are required to take special measures to control all discharges of cadmium, including cadmium pigments.

The European Directive 91/338/EEC restricts the use of cadmium pigments in certain polymers, depending on the purpose of use. In 1996 use in coating media was prohibited. Use in artists' colours and ceramic products is still permitted. There is no restriction on the use of cadmium pigments for toys, providing that the pigmented article meets the European standard EN 71 part 3. Cadmium pigments may be used in food contact polymers provided that the cadmium pigments satisfy the purity standards in the different European states. The standard for soluble cadmium is 0.01 % by weight.

Information -

We have described our product concerning possible safety requirements by the above mentioned information given to the best of our knowledge and experience. All data given are never meant to guarantee any quality description nor product properties.